

# SONIC DIGITAL HS2

## CLEANING GENERATOR

The Sonic Digital HS2 delivers up to 2,000 W. Flexible and space-saving mounting options, high degree of efficiency, and compatibility with other components makes the Sonic Digital HS2 the perfect solution for industrial installations.



### COMPATIBILITY

- Rod transducer
- Plate transducer
- Submersible transducer

### POWER CONNECTION

Supply

- Loose wires or country-specific plug
- Germany: Safety contact plug (Schuko)

Device

- Phoenix

### WEIGHT & DIMENSIONS

- 3.75 kg
- H x W x D: 385 x 169 x 89 mm



### TECHNOLOGIES, FUNCTIONS, BENEFITS

- Sonic Digital technology for easy integration through DIN rail mounting
- Sweep (with plate and submersible transducers from 80 kHz)
- Digital creation and control of frequency with 32-bit micro controller
- Power adjustment 10–100% in steps of 1% with plate and submersible transducers (50–100% with rod transducers)
- Frequency monitoring
- Fan control
- Temperature management
- Dry-run protection if used with Sonopush rod transducers
- 15-pole I/O interface
- Optional: Set-up and control via Sonic Digital manual operating unit or Sonic Digital user interface
- Optional RS-485 interface
- Optional PROFIBUS or PROFINET interface



### FREQUENCY & POWER

	300 W	400 W	500 W	600 W	750 W	800 W	1,000 W	1,200 W	1,500 W	2,000 W
25 kHz	■	■	■	■○	■	■	■○	■○	■○	■○
30 kHz	■	■	■	■○	■	■	■○	■○	■○	■
40 kHz	■○	■	■○	■	■○	■	■○	■○	■	■
58 kHz	■	■	■	■	■	■	■	■	■	■
80 kHz	■	■	■	■	■	■	■			
120 kHz	■	■	■	■	■	■	■			
132 kHz	■	■	■	■	■	■	■			

Values for 230 V supply voltage. 115 V supply voltage values upon request.

■ Plate & submersible transducers ○ Rod transducer



WEBER  
ULTRASONICS

WEBER-ULTRASONICS.COM